
Sliding Door


Door Track Cover Trim	(Door Track)
Door size. Height 2" less than opening Width 3" more than opening	(Top Rail)
Door track (K) Door track (opening size x 2) length pcs (O) Track splice collar (1 per splice) pcs (L) Track brackets (24" on center)	Door Girts 2" less than door
pcs (M) Track cover (10'6") pcs	opening
(N) Track end cap (2 per track run) pcs (P) Trolley (2 per door) style pcs	Bottom Rail
	3" more than
Door rails	door opening
(A)Side rail (length of door heigth)(2 per door)	
lengthpcs	
(B)Bottom rail (length of door width)(1 per door)	Installation Tips
length pcs (E)Door girts (length of door width)(24" o.c.)	mstanation rips
length pcs	See CannonBall sliding door parts page for complete list of products.
Door guides	
(D) Stay rollers (1 per door)	Door track length is to be double the width of
pcs	the opening size.
(F) Door latches (2 per door)	
pcs	Single trolleys will support a door up to 450lbs.
(G) Door handles (1 per door)	
pcs (C) Jamb mount stop (1 per door) pcs	When using 2x4 lumber for side rails, use a 1.5"x3.5" angle trim to cover the 2x4 side rails & botttom rail. Also use j-channel trim on each side rail.
(when using stay guide rail system,use jamb mount stop for the door stop)(D) Stay guide rail (length needs to be60% of the width of door)	When using stay guide rail system, use jamb mount door stop and you need only one door latch.

(use with alum. bottom door rail)


length_____pcs. ____

Sliding Door





CannonBall Sliding Door



Single Sliding Door

- * 2 verticals A
- * 1 bottom rail **B** with rear stop **C**
- * 1 stay guide for at least 60% of the door width **D** or 1 stay roller **D**
- * steel or wood horizonals. (E) (one for every 2 feet of height)
- * 2 door latches
- * 1 door pull **G**

Double Sliding Door

- * 3 verticals A
- * 1 coupling vertical **H**
- * 2 bottom rail **B** with rear stop **C**
- * 2 stay guide for at least 60% of the door width **D** or 2 stay rollers **D**
- * steel or wood horizonals. (one for every 2 feet of heightfor each door section)
- * 2 door latches
- * 1 center snugger
- * 1 door pull **G**
- * 1 center guide **1**

Track

- * track should be twice the width of the door opening
- * 1 track bracket for every two feet of track
- * track cover **M** should be same length as the track
- * 2 end caps N per track run
- * splice collar **1** per each track splice

Trolleys

- * a single sliding door requires 2 trolleys P
- * a split sliding door requires 4 trolleys P

Sliding Door Products

CannonBall Key Hole Door Track



Available Lengths 8'Track (643836) 10'Track (643837) 12"Track (711061) 14"'Track (711062) 16'Track (711063)

Track Cover see trim page B. 10

Track Splice Collar

(711207)


Collar slips over door track to ensure a continual track



Ceiling Track Bracket (646602)

Ceiling mount track bracket mounts a track to ceiling. One required for every 2 ft. of track

Door Track Mounting Brackets



Track & Cover Bracket (646513)

Face mount bracket holds track and cover one required for every 2 ft. of track



Track Bracket (711216)

> Face mount bracket holds track. One required for every 2 ft. of track



Double Track Bracket (646801)

Face mount double track bracket holds track.

Can be used with a double track cover One required for every 2 ft. of track

Door Trolleys

6 1/4" Bolt Trolley (643428) **Delrin Rollers** Supports a door up to 450 lb. Pendant bolt allows for 4 way adjustment.



9 1/4" Bolt Trolley (643428)

Delrin Rollers Supports a door up to 450 lb. Pendant bolt allows for 4 way adjustment.



Double Truck Trolley (643437)

Supports a door up to 800 lb. Pendant bolt allows for 4 way adjustment Bolt is not included. Use (462033)

Door Guides & Rollers



Stay Guide Roller (711457)

Adjustable roller keeps the keeps the door in place.



Holds the split door when the doors are in the closed position. Mounts to concrete with anchors.



Center Guide Half (710950)

Holds the split door when the doors are in the closed position. Mounts to concrete with anchors.



Door Stops

Door Stop (711453) Stops and holds doors up to 2" in thickness



Adjustable Door Guide

(651404)

White Alums. Adjustable for door thickness 2.5"-6"

Jamb Mount Stop (751456)

Mounts to the door jamb and holds the door in both the open and closed position. No mounting screws included.



Cam Latch (711506)

Mounts to the jamb and keeps the door snug to the frame.




Door Jamb Latch (728106) Mounts to the jamb and keeps the door snug to the frame.



Door Snugger (751456)


Mount to a split sliding door and keeps the doors togather.



Track End Cap (711209)Mounting bolt included



Door Handle (711503)White Painted No screws included



9 1/4" Pendant Bolt (462033) Bolt for truck trolley 4 way adjustment with adjusting nut

Track Cover End Trim (646515)Two per track run,

one for each end. Fastens to end of track to close off the end.


Note: See dcmetal.com for installation manuals.

Sliding Doors Products

Vertical Door Rail #100 AV

(100AVxx)

White Painted Aluminum For 1.5" door. Designed for wooden 2x4, 2x6 or steel girts Lengths: 8'-10'-12'-14'-16'-18'-20'




Vertical Door Rail #116 HV (116HVxx)

White Painted Aluminum
For 1.5" door.
Designed for wooden 2x4, 2x6 or steel girts
Designed to couple with #100 AV rails
on double doors

Lengths: 8'-10'-12'-14'-16'-18'-20'

Bottom Door Rails #244 BR



White Aluminum
For 1.5" door.
Mates with #64 stay guide system
Eliminates bottom wood rail
Available lengths: 8'-10'-12'-14'-16'-18'-20'

Bot

Bottom Door Rails #201 AB


White Aluminum (201ABxx)
For 1.5" door.
Use with stay roller & door stop
Use with wood 2x4, 2x6 or steel girts
Available lengths: 8'-10'-12'-14'-16'-18'-20'


Vertical Door Rail #391 BV

(391BVxx)

White Painted Aluminum
For 3.5" door.
Designed for wooden 2x4 or steel girts
Available lengths: 8'-10'-12'-14'-16'-18'-20'








Vertical Door Rail #396 HV

(396HVxx)


White Painted Aluminum
For 3.5" door.
Designed for wooden 2x4 or steel girts
Designed to couple with #391BV rails
on double doors
Available lengths: 8'-10'-12'-14'-16'-18'-20'

Bottom Door Rails

#394BR (394BRxx)



White Aluminum
For 3.5" door.
Mates with #64 stay guide system
Eliminates bottom wood rail
Available lengths: 8'-10'-12'-14'-16'-18'-20'



Steel Girt # 235 BG (BG235xx)

Steel galvanized box girt G90 coating 20 gauge steel Designed to replace wooden girts on sliding doors Available lengths: 8'-10' 12'-14'-16'-18'-20'-22'-24'


Stay Guide Rail #64

(SG164xx)


Mounting Bracket ->



16 gauge steel
Mounting hardware included
Mates with #244 bottom rail-#394 BR Bottom Rail
(Engages with bottom rail to keep the door from blowing out)
Available lengths: 6'-8'-10'



Center Guide



For a double sliding door Attaches to a 6x6 treated post Mates with #244 bottom rail & #394 BR Bottom Rail (Engages with bottom rail to keep the double doors from blowing out in the closed position) Single 6x6 post (SDR1601) Double 6x6 post (SDR1602)