



# ENTRY DOOR

## PRODUCT GUIDE

*Applications for all building markets:*



# 1700- /1800-SERIES

## 1700-SERIES (1734, 1741, 1751 & 1795 Models)

### Economical rolled edge utility door.

A general utility door for agricultural buildings, our 1700-Series doors have the features you need. With a panel that is 1-3/4" thick, you can easily use standard door accessories. These pre-painted, pre-hung doors feature a rolled-edge panel, 24-gauge (1741 & 1751) or 26-gauge (1734 & 1795) steel skins and a polyurethane core — a sturdy, durable choice.

### FEATURES:

- An economical solution for general utility agricultural use.
- Pre-hung and pre-painted for fast installation and a finished look.
- Standard 1-3/4" thick panel easily works with window lites, door closers & other accessories -- and factory installation of options saves on job site hassles.



1700-Series  
(1734 and 1795)

## 1800-SERIES (1852, 1853, 1872 & 1873 Models)

### Economical capped edge utility door.

With its sturdy capped edge panel, 1-5/8" thickness and multiple skin choices – from 30-gauge steel to fiberglass – our 1800-Series doors offer a wide range of economical options for agricultural environments.

### FEATURES:

- 30-gauge steel, aluminum or fiberglass panel skins for various conditions, such as moderate moisture or livestock containment.
- Prefinished white panel with mill or white frame for a low maintenance door that doesn't require painting.
- Options include window lites specifically made for this door thickness.



1800-Series  
(1852, 1853, 1872 and 1873)






[www.cnbhnp.com](http://www.cnbhnp.com)



The rolled edge on the 1700-Series gives the door a commercial and finished look.



The 1795 has a dual contact jamb weatherstrip for improved weather sealing.



The 1800-Series features a capped edge panel for enhanced durability.

**1700 & 1800-SERIES DOORS TECHNICAL SPECIFICATIONS**

FEATURE	MODEL					
	1734	1741	1751	1795	1852/1872	1853/1873
<b>DOOR PANEL</b>						
Edge Type	Rolled	Rolled	Rolled	Rolled	Capped	Capped
Thickness	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-5/8"	1-5/8"
Skin Type	26 ga. Steel (40 size is 24 ga. smooth)	24 ga. Steel	24 ga. Steel	26 ga. Steel (40 size is 24 ga. smooth)	30 ga. Steel (AL or Fiberglass Option)	30 ga. Steel (AL or Fiberglass Option)
Textured skin	✓	✓	✓	✓	✓	✓
Standard Color	White	White	White	White	White	White
Pre-painted & Pre-hung	✓	✓	✓	✓	✓	✓
Universal Swing	✓	✓	✓	✓	✓	✓
No Wood Blocking	✓	✓	✓	✓		
Polyurethane Insulated Core	✓	✓	✓	✓	✓	✓
Door Sweeps Top & Bottom	Dual Bulb	Three-fin Bulb	Three-fin Bulb	Dual Bulb	Pile Weatherstrip	Pile Weatherstrip
<b>DOOR JAMB</b>						
Depth	1-15/16"	3-1/2"	3-1/2"	3-1/2"	3-1/2"	3-1/2"
Material	Aluminum	Aluminum	16 ga. Steel	16 ga. Steel	Aluminum	Aluminum
Finish	White	White	White	White	White	Mill
Pre-painted	✓	✓	✓	✓	✓	
Weathersealing	Pile Weatherstrip	Adhesive Strip	Adhesive Strip	Dual Contact	Pile Weatherstrip	Pile Weatherstrip
ADA Compliant Header/Threshold	✓			✓	N/A	N/A
Standard Nailing Flange	✓				1872 Only	1873 Only
Adjustable Strike Plate	✓	✓	✓	✓	✓	✓
<b>LOCKSET FEATURES</b>						
Lockset Insert	Non-Collapsible Nylon	Non-Collapsible Nylon	Non-Collapsible Nylon	Non-Collapsible Nylon	Wood	Wood
2-3/4" Backset	✓	✓	✓	✓	✓	✓
2-1/8" Bore	✓	✓	✓	✓	✓	✓
<b>HINGES</b>						
4x4" Stainless NRP Hinges	✓	✓	✓	✓	✓	✓
<b>DOOR SIZE</b>						
2868	Standard	Standard	Standard	Standard	Standard	Standard
3068	Standard	Standard	Standard	Standard	Standard	Standard
4068	Standard	Standard	Standard	Standard	Standard	Standard
6068	Custom Option	Standard	Standard	Standard	Standard	Standard
<b>OPTIONS / ACCESSORIES</b>						
Accessories Factory Installed	✓	✓	✓	✓	✓	✓
Subframe for Steel Buildings				✓		
Snap Cap					✓	✓
J Trim Header					✓	✓
Prep for Panic and closer	✓	✓	✓	✓	✓	✓
Prep for Deadbolt	✓	✓	✓	✓	✓	✓
Standard Window Lites (See chart on back page for options)	✓	✓	✓	✓	✓	✓

## OUT-TO-OUT DIMENSIONS

CALL SIZE*	DOOR MODEL OR SERIES (IF LISTED AS SERIES, ALL MODELS IN THAT SERIES HAVE SAME DIMENSIONS)													
	1734	1741	1751	1795	1822	1852, 1853 1872, 1873	1900- Series	2004AL	2004AF	2004ST & 2004STB	2005- Series	2006- Series	2007	2008
<b>68 HEIGHT</b>														
2868	32-13/16" x 80-5/8"					33-9/16" x 81-3/4"	36" x 81-5/16"	33-5/16" x 81-1/8"		34-5/8" x 80-5/8"	35-13/16" x 80-5/8"		N/A	N/A
3068	36-13/16" x 80-5/8"	37-9/16" x 81-3/16"	38" x 81-3/16"	39-13/16" x 80-5/8"	37-3/16" x 81-5/16"	37-9/16" x 81-3/4"	40" x 81-5/16"	37-5/16" x 81-1/8"	37-1/16" x 80-5/8"	38-5/8" x 80-5/8"	39-13/16" x 80-5/8"	39-13/16" x 82"	36-1/2" x 80-3/8"	40" x 82"
4068	46-13/16" x 80-5/8"	49-9/16" x 81-3/16"	50" x 81-3/16"	49-13/16" x 80-5/8"	49-3/16" x 81-5/16"	49-9/16" x 81-3/4"	52" x 81-5/16"	47-5/16" x 81-1/8"	47-1/16" x 80-5/8"	48-5/8" x 80-5/8"	49-13/16" x 80-5/8"	49-13/16" x 82"	N/A	
6068				69-13/16" x 80-5/8"		74-3/16" x 81-3/4"	77-1/4" x 81-5/16"	74-5/16" x 81-1/8"	74-1/16" x 80-5/8"	74-7/8" x 81-3/8"	76-3/16" x 82"	76-3/16" x 82"	N/A	76" x 82"
<b>70 HEIGHT</b>														
3070											39-13/16" x 84-5/8"	39-13/16" x 86"	36" x 84-3/8"	40" x 86"
4070											49-13/16" x 84-5/8"	49-13/16" x 86"	N/A	52" x 86"
6070											76-3/16" x 86"	76-3/16" x 86"	N/A	76" x 86"
8070													N/A	100" x 86"

\* Also available custom order for most models: 2068, 2668, 3060

## STANDARD WINDOW LITE SIZES

WINDOW LITE STYLE AND SIZE	OPTIONS				
	1 Lite	9 Lite	Insulated Glass	Non-Insulated Glass	Thickness
<b>IMI FRAME</b>					
22x36"	✓	✓	✓		1-5/8" or 1-3/4"
<b>ALUMINUM FRAME</b>					
6x42"	✓		✓	✓	1-5/8" or 1-3/4"
16x16"	✓		✓		1-5/8" or 1-3/4"
20x24"	✓	✓	✓	✓	1-5/8" or 1-3/4"
22x36"	✓	✓	✓		1-5/8" or 1-3/4"
22x64"	✓				1-5/8" or 1-3/4"
<b>PVC FRAME</b>					
16x16"	✓		✓		1-3/4"
20x24"	✓	✓	✓		1-3/4"
22x30"	✓	✓	✓		1-3/4"
22x36"	✓	✓	✓		1-3/4"
22x64"	✓		✓		1-3/4"



REV. 02/19